

FERTILIZER TENDERS

At Brehmer, we're proud to be a partner to the agriculture industry. We know the importance of correct fertilizer application and the roll it plays in your operation. That's why we build with quality materials and implement time and cost-saving features. We build each tender box to suite your needs by asking the right questions at the start of a project.

SIDE DISCHARGE

FEATURES:

 Self-Locking Hydraulic Discharge Auger

OPTIONS:

- Split Bins
- Diesel or Wet Kit Available
- Stainless Steel Fenders

COLOR OPTIONS:





Stainless Steel

Brehmer Gray

TRUCK MOUNT



TENDER SIZE	16' 18'		20'	
Travel Height	7′2″			
Auger Length	16′7″			
Discharge Height - MIN	7′1″			
Discharge Height - MAX	14'2"			
Auger Reach - SIDE	13′4″			
Standard Cubic Feet	569 663		711	
6" Taller Cubic Feet	633 735		791	

Discharge height is measured from the top of the existing truck frame.

TRAILER MOUNT



TENDER SIZE	20'	24'	28'	32'
Travel Height	10'8"			
Auger Length	16′7″			
Discharge Height - MIN	10′7″			
Discharge Height - MAX	17′8″			
Auger Reach - SIDE	13'4"			
Standard Cubic Feet	711	854	996	1138
6" Taller Cubic Feet	791	950	1107	1265

All Brehmer Fertilizer Tenders are built with:

EZ Slide Gate System

- Run gates full-open without clogging

LOW Center of Gravity

- Unique to Brehmer Tenders
- Increases safety, decreases rollovers

304 Stainless Steel Bin Construction and Auger Flighting

Filled-In Tarp Bow System
Individual Hopper Ladders
Reinforced Corner Gussets
Unloading Capacity of 3500-4000 lbs/min
Grease Banks
Unique Bearing Design
2" Clean-Outs

OVERHEAD DISCHARGE

FEATURES:

- Top-Mounted Orbital Motor on the Vertical Auger
- 270° Rotation Auger System
- 10" Belly, 13" Vertical, 10" Discharge

OPTIONS:

- Split Bins
- Diesel or Wet Kit Available
- Stainless Steel Fenders

COLOR OPTIONS:





Stainless Steel

Brehmer Gray

TRUCK MOUNT



TENDER SIZE	16' 18'		20'	
Travel Height	8′10″″			
Auger Length	16′10″			
Discharge Height - MIN	7′2″			
Discharge Height - MAX	17′8″			
Auger Reach - SIDE	13′7″			
Auger Reach - REAR	14′7″			
Standard Cubic Feet	569	663	711	
6" Taller Cubic Feet	633 735		791	

Discharge height is measured from the top of the existing truck frame.

24' Overhead Discharge Mounted on a 45' Trailer Mount

TENDER SIZE	20'	24'	28'	32'
Travel Height	12'4"			
Auger Length	16′10″			
Discharge Height - MIN	10'8"			
Discharge Height - MAX	21′3″			
Auger Reach - SIDE	13'8"			
Auger Reach - REAR	14′7″			
Standard Cubic Feet	711	854	996	1138
6" Taller Cubic Feet	791	950	1107	1265



This new 5' Bin Series tender from Brehmer design performs like the Brehmer Dry Tenders you've come to depend on, but features a new bin design. The base model is built with 304 stainless steel and comes with the standard features listed below, but can be customized with a variety of optional add-ons.

STANDARD FEATURES:

- Manual tarp standard on Side Discharge
- Electric tarp standard on Overhead Discharge
- Three five-foot bins 15' Box
- Four five-foot bins 20' Box
- Filled-in tarp bow system
- Unloading capacity of 3500-4000 lbs/min

- Stainless steel auger flighting
- Reinforced corner gussets
- Dual EZ Slide gates on each bin
- Self-locking hydraulic discharge auger
- 10" belly and discharge auger on all units. 13" vertical auger on overhead discharge

OPTIONS:

- Truck pump
- Stainless bumper and fenders with full lights
- Middle bin split
- Stainless steel frame

COLOR OPTIONS:





Stainless Steel

Brehmer Gray

	SIDE DISCHARGE		OVERHEAD DISCHARGE	
TENDER SIZE	15'	20'	15'	20'
Travel Height	7'2"		8′10″	
Auger Length	16′7″		16′10″	
Discharge Height - MIN	7′1″		7′2″	
Discharge Height - MAX	14'2"		17′8″	
Auger Reach - SIDE	13′4″		13′7″	
Auger Reach - BACK	N/A		14′7″	
Standard Cubic Feet	600	790	600	790
Standard Number of Bins	3	4	3	4

Discharge height is measured from the top of the existing truck frame.

NURSE TRAILERS

STANDARD FEATURES ON ALL NURSE TRAILERS:

- Moveable pocket ladder can be mounted at various points on center platform for easy access
- Treated 2x12 Douglas fir decking
- Spring ride suspension (optional air ride suspension)

STAINLESS STEEL TANK NURSE TRAILER:

• Stainless steel fenders

POLY TANK NURSE TRAILER:

- Pre-drilled mounting holes for popular poly tanks like Enduraplas and Ace Tanks
- Adjustable center support for end sump tanks

	POLY TANK NURSE TRAILER		STAINLESS STEEL NURSE TRAIL			
TRAILER SIZE	42'	45'	48'	42'	45'	48'
Front Platform	12′	12′	12′	-	-	-
Middle Platform	16′	19′	22′	16′	19′	22′
Back Platform	12′	12′	12′	-	-	-

Stainless Steel Tank Nurse Trailer front and back platforms can be customized for the size of your stainless steel tank.

Increase your versatility for liquid fertilizer applications with a **Nurse Trailer** from Brehmer Mfg. Our Poly Tank and Stainless Steel Tank Nurse Trailers feature front and back platforms with adjustable center support for sump tanks and a moveable pocket ladder that can be positioned at various points along the center platform for easy access.







FIELD LOADER CONVEYORS



FL1024

Featuring 304 stainless steel undercarriage and framework, this field loader boasts a drive wheel with power steering.



Hydraulic driven and steerable drive wheel

STANDARD FEATURES:

- 20 HP Honda engine, electric start
- 24" wide crescent top belt with stainless steel lacing
- 30° Incline
- 1" bearings
- 13' 3" discharge height
- Direct hydraulic driven crowned and lagged drive pulley
- Self-aligning belt-tightening system (Patent Pending)
- 304 stainless steel undercarriage and framework

- Hydraulic driven and steerable drive wheel
- 205/75R 15" tires
- Variable belt speed
- Low profile 10" horizontal hopper
- 25'6" incline
- 4' folding hopper
- Adjustable discharge chute
- Tow hitch with 1" clevis and safety chains
- 8 gallon gas tank

OPTIONS:

- Stainless steel weather covers
- Enclosed discharge spout





FL1030

Ruggedly designed to work in any environment, the FL1030 Field Loader from Brehmer Mfg. is designed to handle your ag lime and fertilizer loading needs.





Remote controlled belt and tow hitch.



Optional hopper skirting

STANDARD FEATURES:

- Wireless remote RPM and belt on/off
- Start/stop with a fully loaded belt
- Duetz 2.9L engine, electric start
- 30" wide belt
- 25° Incline
- 2" bearings
- Direct hydraulic driven crowned drive pulley
- Self-aligning belt-tightening system (Patent Pending)
- Variable belt speed
- 10' hopper
- 13' 11" discharge height

- 12' 6" roller height
- Tow hitch with 1" clevis and safety chains (Pintle hitch, optional)
- Wireless remote hydraulic powered raise/lower hitch
- 38" max hitch height
- 44' 2" overall length
- 13' 2" travel height
- Brake and turn lights, 7-way RV plug
- 255/70 R22.5 tires
- 7,100 lbs total wt. (1,060 lbs tongue wt.)
- 30 gallon fuel tank
- 34 gallon hydraulic reservoir

OPTIONS:

• Hopper Skirting





FLX 1224

Transition between fertilizer and lime with the dual purpose FLX1224 Field Loader from Brehmer Mfg. The lime hopper easily disassembles and converts for low-profile loading of fertilizer.



The lime hopper converts for low profile loading for fertilizer.



Don't need a full lime hopper? Order the FLX1224 standard fertilizer package.

STANDARD FEATURES:

- Start/stop with a fully loaded
- 25 HP Honda engine, electric
- 24" crescent top belt with stainless steel lacing
- 25° Incline
- Direct hydraulic driven crowned and lagged drive pulley
- Self-aligning belt-tightening system (Patent Pending)
- Hydraulic driven and steerable drive wheel
- Variable belt speed

- 14' 10" discharge height
- 14' clearance under top drive pulley
- Adjustable discharge chute
- Adjustable tow hitch with 1" clevis and safety chains (Pintle hitch, optional)
- Brake and turn lights, 7-way RV plug
- 8 gallon gas tank
- 304 stainless steel

OPTIONS:

• Choose from the Lime Hopper or the Standard Fertilizer package.

