

# Brehmer



## FERTILIZER EQUIPMENT

DRY FERTILIZER TENDERS,  
FIELD LOADERS & NURSE TRAILERS



# FERTILIZER TENDERS

At Brehmer, we're proud to be a partner to the agriculture industry. We know the importance of correct fertilizer application and the roll it plays in your operation. That's why we build with quality materials and implement time and cost-saving features. We build each tender box to suite your needs by asking the right questions at the start of a project.

## SIDE DISCHARGE

### FEATURES:

- Self-locking hydraulic discharge auger

### OPTIONS:

- Split bins
- Diesel or wet kit available
- Stainless steel fenders

### COLOR OPTIONS:



Stainless  
Steel



Brehmer  
Gray

## TRUCK MOUNT



18' Side Discharge Truck Mount

TENDER SIZE	16'	18'	20'
Travel Height	7'2"		
Auger Length	16'7"		
Discharge Height - MIN	7'1"		
Discharge Height - MAX	14'2"		
Auger Reach - SIDE	13'4"		
Standard Cubic Feet	569	633	711
6" Taller Cubic Feet	633	704	791

Discharge height is measured from the top of the existing truck frame.

## TRAILER MOUNT



24' Side Discharge Mounted  
on a 45' Trailer

TENDER SIZE	20'	24'	28'	32'
Travel Height	10'8"			
Auger Length	16'7"			
Discharge Height - MIN	10'7"			
Discharge Height - MAX	17'8"			
Auger Reach - SIDE	13'4"			
Standard Cubic Feet	711	854	996	1138
6" Taller Cubic Feet	791	950	1107	1265

All Brehmer Fertilizer Tenders are built with:

**EZ Slide gate system**

- Run gates full-open without clogging

**LOW center of gravity**

- Unique to Brehmer Tenders
- Increases safety, decreases rollovers

**304 Stainless steel bin construction and auger flighting**

**Filled-in tarp bow system**

**Individual hopper ladders**

**Reinforced corner gussets**

**Unloading capacity of 3500-4000 lbs/min**

**Grease banks**

**Unique bearing design**

**2" Clean-outs**

# OVERHEAD DISCHARGE

**FEATURES:**

- Top-mounted orbital motor on the vertical auger
- Bottom vertical spinner bearing (Patent Pending)
- 270° rotation auger system
- 10" belly, 13" vertical, 10" Discharge

**OPTIONS:**

- Split bins
- Diesel or Wet Kit Available
- Stainless Steel Fenders

**COLOR OPTIONS:**



Stainless Steel



Brehmer Gray

## TRUCK MOUNT



18' Overhead Discharge Truck Mount on Mild Steel Frame With Stainless Steel Fenders

**NEW! TOP MOUNTED ORBITAL MOTOR ON ALL UNITS.**

TENDER SIZE	16'	18'	20'
Travel Height	8'10"		
Auger Length	16'10"		
Discharge Height - MIN	7'2"		
Discharge Height - MAX	17'8"		
Auger Reach - SIDE	13'7"		
Auger Reach - REAR	14'7"		
Standard Cubic Feet	569	633	711
6" Taller Cubic Feet	633	704	791

Discharge height is measured from the top of the existing truck frame.

## TRAILER MOUNT



24' Overhead Discharge Mounted on a 45' Trailer Mount

TENDER SIZE	20'	24'	28'	32'
Travel Height	12'4"			
Auger Length	16'10"			
Discharge Height - MIN	10'8"			
Discharge Height - MAX	21'3"			
Auger Reach - SIDE	13'8"			
Auger Reach - REAR	14'7"			
Standard Cubic Feet	711	854	996	1138
6" Taller Cubic Feet	791	950	1107	1265





15' Side Discharge Truck Mount

## NEW! 5' BIN SERIES TRUCK OR TRAILER

This new 5' Bin Series tender from Brehmer design performs like the Brehmer Dry Tenders you've come to depend on, but features a new bin design. The base model is built with 304 stainless steel and comes with the standard features listed below, but can be customized with a variety of optional add-ons.

### STANDARD FEATURES:

- Manual tarp standard on Side Discharge
- Electric tarp standard on Overhead Discharge
- Three five-foot bins - 15' Box
- Four five-foot bins - 20' Box
- Filled-in tarp bow system
- Unloading capacity of 3500-4000 lbs/min
- Stainless steel auger flighting
- Reinforced corner gussets
- Dual EZ Slide gates on each bin
- Self-locking hydraulic discharge auger
- 10" belly and discharge auger on all units. 13" vertical auger on overhead discharge
- Bottom vertical spinner bearing on overhead discharge (Patent Pending)

### OPTIONS:

- Truck pump
- Stainless bumper and fenders with full lights
- Middle bin split
- Stainless steel frame



20' Side Discharge Mounted on a 32' Trailer

### COLOR OPTIONS:



Stainless Steel



Brehmer Gray

TENDER SIZE	SIDE DISCHARGE		OVERHEAD DISCHARGE	
	15'	20'	15'	20'
Travel Height	7'2"		8'10"	
Auger Length	16'7"		16'10"	
Discharge Height - MIN	7'1"		7'2"	
Discharge Height - MAX	14'2"		17'8"	
Auger Reach - SIDE	13'4"		13'7"	
Auger Reach - BACK	N/A		14'7"	
Standard Cubic Feet	600	790	600	790
Standard Number of Bins	3	4	3	4

Discharge height is measured from the top of the existing truck frame.



# NURSE TRAILERS

Increase your versatility for liquid fertilizer applications with a **Nurse Trailer** from Brehmer Mfg. Our Poly Tank and Stainless Steel Tank Nurse Trailers feature front and back platforms with adjustable center support for sump tanks and a movable pocket ladder that can be positioned at various points along the center platform for easy access.

## STANDARD FEATURES ON ALL NURSE TRAILERS:

- Movable pocket ladder can be mounted at various points on center platform for easy access
- Treated 2x12 Douglas fir decking
- Spring ride suspension (optional air ride suspension)

## STAINLESS STEEL TANK NURSE TRAILER:

- Stainless steel fenders

## POLY TANK NURSE TRAILER:

- Pre-drilled mounting holes for popular poly tanks like Enduraplas and Ace Tanks
- Adjustable center support for end sump tanks



45' Stainless Steel Tank Nurse Trailer. Tanks and mixing station installed by a certified Brehmer Dealer.



42' Poly Tank Nurse Trailer. Tanks and mixing station installed by a certified Brehmer Dealer.

TRAILER SIZE	POLY TANK NURSE TRAILER			STAINLESS STEEL TANK NURSE TRAILER		
	42'	45'	48'	42'	45'	48'
Front Platform	12'	12'	12'	-	-	-
Middle Platform	16'	19'	22'	16'	19'	22'
Back Platform	12'	12'	12'	-	-	-

*Stainless Steel Tank Nurse Trailer front and back platforms can be customized for the size of your stainless steel tank.*



# FIELD LOADER CONVEYORS



## FL1024

### **PATENTED**

US Patent. No. US 12,338,075 B2

Featuring 304 stainless steel undercarriage and framework, this field loader boasts a drive wheel with power steering.



*Hydraulic driven and steerable drive wheel*

### **STANDARD FEATURES:**

- 20 HP Honda engine, electric start
- 24" wide crescent top belt with stainless steel lacing
- 30° Incline
- 1" bearings
- 13' 3" discharge height
- Direct hydraulic driven crowned and lagged drive pulley
- Patented self-aligning belt system that centers the conveyor belt as the machine is being used
- 304 stainless steel undercarriage and framework
- Hydraulic driven and steerable drive wheel
- 205/75R 15" tires
- Variable belt speed
- Low profile 10" horizontal hopper
- 25'6" incline
- 4' folding hopper
- Adjustable discharge chute
- Tow hitch with 1" clevis and safety chains
- 8 gallon gas tank

### **OPTIONS:**

- Stainless steel weather covers
- Enclosed discharge spout





# FL1030

## PATENTED

US Patent. No. US 12,338,075 B2

Ruggedly designed to work in any environment, the FL1030 Field Loader from Brehmer Mfg. is designed to handle your ag lime and fertilizer loading needs.



Remote controlled belt and tow hitch.



Optional hopper skirting

## STANDARD FEATURES:

- Wireless remote RPM and belt on/off
- Start/stop with a fully loaded belt
- Duetz 2.9L engine, electric start
- 30" wide belt
- 25° Incline
- 2" bearings
- Direct hydraulic driven crowned drive pulley
- Patented self-aligning belt system that centers the conveyor belt as the machine is being used
- Variable belt speed
- 10' hopper
- 13' 11" discharge height
- 12' 6" roller height
- Tow hitch with 1" clevis and safety chains (Pintle hitch, optional)
- Wireless remote hydraulic powered raise/lower hitch
- 38" max hitch height
- 44' 2" overall length
- 13' 2" travel height
- Brake and turn lights, 7-way RV plug
- 255/70 R22.5 tires
- 7,100 lbs total wt. (1,060 lbs tongue wt.)
- 30 gallon fuel tank
- 34 gallon hydraulic reservoir

## OPTIONS:

- Hopper Skirting
- Three-piece, removable grizzly bar set



# FLX 1224

**PATENTED**

US Patent. No. US 12,338,075 B2



The lime hopper converts for low profile loading for fertilizer. **Don't need a full lime hopper?** Order the FLX1224 standard fertilizer package.



Reduce clogging in your spreader with our optional grizzly bar set.

Transition between fertilizer and lime with the dual purpose FLX1224 Field Loader from Brehmer Mfg. **The lime hopper easily disassembles and converts for low-profile loading of fertilizer.**

## STANDARD FEATURES:

- Start/stop with a fully loaded belt
- 25 HP Honda engine, electric start
- 24" crescent top belt with stainless steel lacing
- 25° Incline
- Direct hydraulic driven crowned and lagged drive pulley
- Patented self-aligning belt system that centers the conveyor belt as the machine is being used
- Hydraulic driven and steerable drive wheel
- Variable belt speed
- 14' 10" discharge height
- 14' clearance under top drive pulley
- Adjustable discharge chute
- Adjustable tow hitch with 1" clevis and safety chains (Pintle hitch, optional)
- Brake and turn lights, 7-way RV plug
- 8 gallon gas tank
- 304 stainless steel
- Torsion axle

## OPTIONS:

- Choose from the Lime Hopper or the Standard Fertilizer package.
- Three-piece, removable grizzly bar set



825 MAIN STREET | LYONS, NEBRASKA 68038

888-687-2655

WWW.BREHMER.COM

06262025-05a