

2020



FERTILIZER EQUIPMENT

DRY FERTILIZER TENDERS,
FIELD LOADERS & NURSE TRAILERS



FERTILIZER EQUIPMENT THAT WORKS AS HARD AS YOU DO.

Brehmer Mfg. has been a family-owned business since 1974, and we plan to keep it that way.

With our humble beginnings in a small 1,500-square-foot space, our founder, Rey Brehmer, made sure that each and every product was designed to improve the work being done in the fields by our customers. Better products. Easier processes. Satisfied customers.

50-plus years later, the Brehmer family is still working to revolutionize the ag equipment industry. Our manufacturing space has expanded to 60,000 square feet, and we use modern fabrication equipment, combined with time-tested techniques and decades of experience, to build the most efficient and trustworthy fertilizer equipment on the market today.



NEW PRODUCT



10' Overhead Discharge Trailer Mount

NEW! 10' TENDER TRAILER OVERHEAD DISCHARGE

Expand your fleet and delivery options with the **NEW 10' trailer** from Brehmer. An all new size of dry fertilizer tender available as a towable, gooseneck trailer. This overhead discharge tender features a new, more efficient bin design that increases clean out efficiency and speed.

STANDARD FEATURES:

- Electric tarp
- 38 HP Kohler Gas Engine
- Tandem axles
- 26,000 lbs carrying capacity
- Top-mounted orbital motor on the vertical auger
- Two five-foot bins
- 270° rotation auger system
- Filled-in tarp bow system
- Unloading capacity of up to 2,000 lbs/min
- Stainless steel auger flighting
- Reinforced corner gussets
- Dual EZ Slide gates on each bin
- 10" belly and discharge auger on all units. 13" vertical auger on overhead discharge
- Bottom vertical spinner bearing on overhead discharge (Patent Pending)
- Stainless bumper and fenders with full lights

COLOR OPTIONS:



Stainless Steel



Brehmer Gray

	OVERHEAD DISCHARGE
TENDER SIZE	10'
Travel Height	11'9"
Auger Length	16'10"
Discharge Height - MIN	5'5"
Discharge Height - MAX	19'10"
Auger Reach - SIDE	14'
Auger Reach - BACK	14'
Standard Cubic Feet	400
Standard Number of Bins	2

Discharge height is measured from the top of the existing truck frame.

OPTIONS:

- Split bins
- Stainless steel frame

* Unloading capacity of up to 5,000 lbs/min of 67 lb material, up to 3,700 lbs/min on 47 lb material.

BREHMER.COM



888-687-2655

FERTILIZER TENDERS

At Brehmer, we're proud to be a partner to the agriculture industry. We know the importance of correct fertilizer application and the roll it plays in your operation. That's why we build with quality materials and implement time and cost-saving features. We build each tender box to suite your needs by asking the right questions at the start of a project.

SIDE DISCHARGE

FEATURES:

- Self-locking hydraulic discharge auger

OPTIONS:

- Split bins
- Diesel or wet kit available
- Stainless steel fenders
- Overhead light package
- Stainless front/back deck & frame

COLOR OPTIONS:



Stainless
Steel



Brehmer
Gray

TRUCK MOUNT



18' Side Discharge Truck Mount

TENDER SIZE	16'	18'	20'
Travel Height	7'2"		
Auger Length	16'7"		
Discharge Height - MIN	7'1"		
Discharge Height - MAX	14'2"		
Auger Reach - SIDE	13'4"		
Standard Cubic Feet	569	633	711
6" Taller Cubic Feet	633	704	791
Number of Bins	4 x 4' Bins	3 x 6' Bins	5 x 4' Bins

Discharge height is measured from the top of the existing truck frame.

TRAILER MOUNT



24' Side Discharge Trailer

TENDER SIZE	20'	24'	28'	32'
Travel Height	10'8"			
Auger Length	16'7"			
Discharge Height - MIN	10'7"			
Discharge Height - MAX	17'8"			
Auger Reach - SIDE	13'4"			
Standard Cubic Feet	711	854	996	1138
6" Taller Cubic Feet	791	950	1107	1265
Number of Bins	5x 4' Bins	6x 4' Bins	7x 4' Bins	8x 4' Bins

All Brehmer Fertilizer Tenders are built with:

EZ Slide gate system made from 304 stainless

- Run gates full-open without clogging

LOW center of gravity

- Unique to Brehmer Tenders

- Increases safety, decreases rollovers

Unloading capacity of up to 5,000 lbs/min of 67lb material, up to 3,700 lbs/min on 47lb material

304 Stainless steel bin construction, auger lighting, and motor/auger couplers

Filled-in tarp bow system

Individual hopper ladders made from 304 stainless

Reinforced corner gussets

Central grease bank station

2" Clean-outs

OVERHEAD DISCHARGE

FEATURES:

- Top-mounted orbital motor on the vertical auger
- Patent Pending bearing design
- 270° rotation auger system
- 10" belly, 13" vertical, 10" Discharge

OPTIONS:

- Split bins
- Diesel or wet kit available
- Stainless steel fenders
- Stainless steel front/back deck & frame
- 19' Discharge auger

COLOR OPTIONS:



Stainless Steel



Brehmer Gray

TRUCK MOUNT



18' Overhead Discharge Truck Mount on Mild Steel Frame With Stainless Steel Fenders

TENDER SIZE	16'	18'	20'
Travel Height	8'10"		
Auger Length	16'10"		
Discharge Height - MIN	7'2"		
Discharge Height - MAX	17'8"		
Auger Reach - SIDE	13'7"		
Auger Reach - REAR	14'7"		
Standard Cubic Feet	569	633	711
6" Taller Cubic Feet	633	704	791
Number of Bins	4 x 4' Bins	3 x 6' Bins	5 x 4' Bins

Discharge height is measured from the top of the existing truck frame.

TRAILER MOUNT



28' Overhead Discharge Mounted on a 45' Trailer

TENDER SIZE	20'	24'	28'	32'
Travel Height	12'4"			
Auger Length	16'10"			
Discharge Height - MIN	10'8"			
Discharge Height - MAX	21'3"			
Auger Reach - SIDE	13'8"			
Auger Reach - REAR	14'7"			
Standard Cubic Feet	711	854	996	1138
6" Taller Cubic Feet	791	950	1107	1265
Number of Bins	5x 4' Bins	6x 4' Bins	7x 4' Bins	8x 4' Bins



15' Side Discharge Truck Mount

5' BIN SERIES TRUCK MOUNTED

The 5' Bin Series of tenders from Brehmer design performs like the Brehmer Dry Tenders you've come to depend on, but with a focus on mobility.

The base model is built with 304 stainless steel, features a new bin design, and comes with the standard features listed below, but can be customized with a variety of optional add-ons.

COLOR OPTIONS:



Stainless Steel



Brehmer Gray

STANDARD FEATURES:

- Manual tarp standard on Side Discharge
- Electric tarp standard on Overhead Discharge
- Three five-foot bins - 15' Box
- Four five-foot bins - 20' Box
- Filled-in tarp bow system
- Unloading capacity of up to 5,000 lbs/min*
- Stainless steel auger flighting
- Reinforced corner gussets
- Dual EZ Slide gates on each bin
- Self-locking hydraulic discharge auger
- 10" belly and discharge auger on all units. 13" vertical auger on overhead discharge
- Bottom vertical spinner bearing on overhead discharge (Patent Pending)

OPTIONS:

- Truck pump
- Stainless bumper and fenders with full lights
- Middle bin split
- Stainless steel frame

TENDER SIZE	SIDE DISCHARGE		OVERHEAD DISCHARGE	
	15'	20'	15'	20'
Travel Height	7'2"		8'10"	
Auger Length	16'7"		16'10"	
Discharge Height - MIN	7'1"		7'2"	
Discharge Height - MAX	14'2"		17'8"	
Auger Reach - SIDE	13'4"		13'7"	
Auger Reach - BACK	N/A		14'7"	
Standard Cubic Feet	600	790	600	790
Standard Number of Bins	3	4	3	4

Discharge height is measured from the top of the existing truck frame.

* Unloading capacity of up to 5,000 lbs/min of 67 lb material, up to 3,700 lbs/min on 47 lb material.

FEATURED PRODUCT



5' BIN - 20' TENDER OVERHEAD DISCHARGE TRAILER MOUNTED

This model features the functionality and mobility of our 5' Bin Series but has all the bells and whistles you need for maximum convenience.

STANDARD FEATURES:

- Top-mounted orbital motor on the vertical auger
- Bottom vertical spinner bearing (Patent Pending)
- 270° rotation auger system
- Electric tarp
- Four five-foot bins
- Filled-in tarp bow system
- Unloading capacity of up to 5,000 lbs/min*
- Dual EZ Slide gates on each bin
- 6" taller sides
- 304 stainless steel auger flighting, bins, motor/ auger couplers
- 19' discharge auger
- Grease banks
- 2" clean-outs
- Reinforced corner gussets
- 10" belly and discharge auger, 13" vertical auger
- Stainless bumper and fenders with full lights
- LED light kit

OPTIONS:

- Wet Kit

* Unloading capacity of up to 5,000 lbs/min of 67 lb material, up to 3,700 lbs/min on 47 lb material.



20' Side Discharge Mounted
on a 32' Trailer

	OVERHEAD DISCHARGE
TENDER SIZE	20'
Travel Height	12'4"
Auger Length	19'
Discharge Height - MIN	7'
Discharge Height - MAX	21'3"
Auger Reach - SIDE	16'
Auger Reach - BACK	17'
Standard Cubic Feet	790
Standard Number of Bins	4

Discharge height is measured from the top of the existing truck frame.

NURSE TRAILERS

Increase your versatility for liquid fertilizer applications with a **Nurse Trailer** from Brehmer Mfg. Our Poly Tank and Stainless Steel Tank Nurse Trailers feature front and back platforms with adjustable center support for sump tanks and a movable pocket ladder that can be positioned at various points along the center platform for easy access.

STANDARD FEATURES ON ALL NURSE TRAILERS:

- Movable pocket ladder can be mounted at various points on center platform for easy access
- Treated 2x12 Douglas fir decking
- Spring ride suspension (optional air ride suspension)

STAINLESS STEEL TANK NURSE TRAILER:

- Stainless steel fenders

POLY TANK NURSE TRAILER:

- Pre-drilled mounting holes for popular poly tanks like Enduraplas and Ace Tanks
- Adjustable center support for end sump tanks



TRAILER SIZE	POLY TANK NURSE TRAILER			STAINLESS STEEL TANK NURSE TRAILER		
	42'	45'	48'	42'	45'	48'
Front Platform	12'	12'	12'	-	-	-
Middle Platform	16'	19'	22'	16'	19'	22'
Back Platform	12'	12'	12'	-	-	-

Stainless Steel Tank Nurse Trailer front and back platforms can be customized for the size of your stainless steel tank.



FIELD LOADER CONVEYORS



FL1024

PATENTED

US Patent. No. US 12,338,075 B2

Featuring 304 stainless steel undercarriage and framework, this field loader boasts a drive wheel with power steering.



Hydraulic driven and steerable drive wheel

STANDARD FEATURES:

- 24.9 HP GX800 Honda engine, electric fuel injected
- 24" wide crescent top belt with stainless steel lacing
- 30° Incline
- 1" bearings
- 13' 3" discharge height
- 25'6" incline
- Direct hydraulic driven crowned and lagged drive pulley
- Patented self-aligning belt system that centers the conveyor belt as the machine is being used
- 304 stainless steel undercarriage and framework
- Hydraulic driven and steerable drive wheel
- 205/75R 15" tires
- Variable belt speed
- Low profile 10' horizontal hopper
- 4' folding hopper
- Adjustable discharge chute
- Tow hitch with 1" clevis and safety chains
- 8 gallon gas tank
- Torsion axle

OPTIONS:

- Stainless steel weather covers
- Enclosed discharge spout
- Break and tail lights, 7-way RV
- 6'6" Fold wing extension

FIELD LOADER CONVEYORS



FL1030

PATENTED

US Patent. No. US 12,338,075 B2

Ruggedly designed to work in any environment, the FL1030 Field Loader from Brehmer Mfg. is designed to handle your ag lime and fertilizer loading needs.



Remote controlled belt and tow hitch.



Reduce clogging in your spreader with our optional grizzly bar set.

STANDARD FEATURES:

- Wireless remote RPM and belt on/off
- Start/stop with a fully loaded belt
- 49HP Duetz engine
- 30" wide belt
- 25° Incline
- 2" bearings
- Direct hydraulic driven crowned drive pulley
- Patented self-aligning belt system that centers the conveyor belt as the machine is being used
- Variable belt speed
- 10' hopper
- 13' 11" discharge height
- 12' 6" roller height
- Tow hitch with 1" clevis and safety chains (Pintle hitch, optional)
- Wireless remote hydraulic powered raise/lower hitch
- 38" max hitch height
- 44' 2" overall length
- 13' 2" travel height
- Brake and turn lights, 7-way RV plug
- 255/70 R22.5 tires
- 7,100 lbs total wt. (1,060 lbs tongue wt.)
- 30 gallon fuel tank
- 34 gallon hydraulic reservoir

OPTIONS:

- Additional remote
- Three-piece, removable grizzly bar set

FIELD LOADER CONVEYORS



FLX 1224

PATENTED

US Patent. No. US 12,338,075 B2



The lime hopper converts for low profile loading for fertilizer. **Don't need a full lime hopper?** Order the FLX1224 standard fertilizer package.



Reduce clogging in your spreader with our optional grizzly bar set.

Transition between fertilizer and lime with the dual purpose FLX1224 Field Loader from Brehmer Mfg. **The lime hopper easily disassembles and converts for low-profile loading of fertilizer.**

STANDARD FEATURES:

- Start/stop with a fully loaded belt
- 24.9 HP GX800 Honda engine, electric fuel injected
- 24" crescent top belt with stainless steel lacing
- 25° Incline
- Direct hydraulic driven crowned and lagged drive pulley
- 304 stainless steel undercarriage and framework
- Patented self-aligning belt system that centers the conveyor belt as the machine is being used
- Hydraulic driven and steerable drive wheel
- Variable belt speed
- 14' 10" discharge height
- 14' clearance under top drive pulley
- Adjustable discharge chute
- Adjustable tow hitch with 1" clevis and safety chains (Pintle hitch, optional)
- Brake and turn lights, 7-way RV plug
- 8 gallon gas tank
- Torsion axle

OPTIONS:

- Choose from the Lime Hopper or the Standard Fertilizer package
- Enclosed discharge spout
- Three-piece, removable grizzly bar set
- Stainless Steel weather covers

SEND US YOUR PICTURES

Send us images of your
Brehmer Equipment in the field
and you could be featured in future
publications!


Visit brehmer.com/photo-submission/ to enter your photos.



Photo from SprayTech Application, Greencastle, PA

ARE YOU SATISFIED WITH YOUR BREHMER EQUIPMENT?

*Take a quick survey and let us know your
thoughts. Scan the QR Code and take our online
survey. You could win custom Brehmer gear!*



825 MAIN STREET | LYONS, NE 68038
888-687-2655
WWW.BREHMER.COM

DEALER CONTACT